TECHNICAL SPECIFICATIONS PERFORMANCE HALL

The Performance Hall has Fixed PA system which cannot be moved comprising of two flown tops and two ground mounted subs. There is a digital snake located upstage right which has 16 inputs and 8 returns. There are a variety of length XLRs and extension leads, as well as ten tall and two short mic stands. There is also an internal induction loop system, please advise in advance if you wish to use this.

SOUND

Mixers

- 1 Behringer X32 Compact
- 1 Behringer S16 Digital Snake

FOH PA

- 2 EV ZX-5 2-way 15" 600w speaker (flown)
- 1 QSC GX-5 500w per channel amplifier
- 2 JBL JRX 118 SP 18" active subwoofer

Monitors

- 4 QSC HPR series active speaker
- 2 FBT X-Pro 112ma
- 2 FBT ProMaxx 114a

Microphones

Wired

- 8 Shure SM58
- 4 Shure SM57

Wireless

- 2 Sennheiser EW 500 G3 belt pack (with lapel or headset)
- 2 Sennheiser EW 100 G3 belt pack (with lapel or headset)
- 1 Sennheiser EW 100 G3 handheld transmitter
- 1 Sennheiser EW 100 G2 handheld transmitter
- 2 Sennheiser EW G4 handheld transmitter

DI

- 2 Tapco DB-1A
- 1 Tapco DB-1P
- 4 Behringer Ultra-DI
- 1 Samson S.direct
- 1 Interspace Industries PCBB2
- 2 Palmer PAN01 Passive



A generic house light rig will be supplied, this includes wash, backlight, side light, colour and specials. We do not hold any specific gels or gobos. If specific lighting or replotting is required, please advise in advance, we cannot guarantee all needs will be catered for if no request is made.

LIGHTING

- 1 ETC Element
- 10 Source 4 Junior
- 7 Source 4 Parnel
- 14 CCT Starlette Fresnel
- 8 LED Par 64 RGB

The in house projector can be connected to from numerous places, including SL and SR floor boxes and the tech box. Audio playback tracks should be provided on either CD or USB memory stick, we won't use internet services for playback.

AV

- 1 Panasonic PT-MZ670L Projector
- 1 Ceiling mounted retractable Projector
- 1 Screen Mac Mini
- 1 Denon DN-V100 DVD Player
- 1 Tascam CD-RW900SL CD Player

The Performance Hall is equipped with single-phase 240V 13A sockets located around the space including 4 sockets in the floor boxes. The grid has an additional three non-dimmable 16A sockets located on each light bar as well as the 48 dimmable 15A sockets.

The performance hall has a capacity of 175 seated or 200 standing. The Theatre stage dimensions are 4m (depth) x 9m (width).

All performance companies using The Performance Hall must ensure and demonstrate (if required) that they can use and operate the theatre's equipment in a safe and competent manner.



RIG PLAN LED Par 64 RGB CCT Starlette Fresnel Source 4 Parnel Source 4 Junior

